# **NV12**

Specifically designed for Air Assist Spray

No ODS

Non-Chlorinated

Nevamar Bond Performance

**High Temperature** 

Resistance

**Fast Tack** 

**Water Resistant** 



NV12 is a high performance and versatile industrial strength contact adhesive. Water resistant and temperature resistant to over 200°F, NV12 is designed for bonding a wide range of substrates to include NEVAMAR decorative laminates and veneers, fiberglass, glass, upholstery, fabrics, foam, auto headliners, cork and particle board.

# PRODUCT USAGE

Nevamar NV12 is designed to be applied to both surfaces about to be joined. Spray an even coat of adhesive with at least 80% to 100% coverage on each surface. Allow to dry 2-4 minutes until tacky. Place the surfaces together and apply pressure evenly across the full bonding surface. For best results: Make sure that the surfaces are dry and free from dirt, grease or oil. Ensure that the adhesives and substrates are at 60°F or higher. If surfaces are porous, a second coat is recommended after the first has dried and become tacky.

#### STORAGE

After use, do not close the valve. Leave the gun and hose connected to the canister. Recommended to store canister off the floor if temperatures below 60°F.

### PHYSICAL PROPERTIES

Appearance: Liquid, clear or red

Specific Gravity: .74 + .03

Shear Adhesion: >100psi and >200°F

Spray Pattern: Web Spray

Flammability: Flammable per ASTM E-681-04

Solvent: Acetone, Cyclohexane

Shelf Life: 15 months

Freezing: Not damaged by freezing but return to

room temp before use.

## PACKAGING

NV12-009C(R)
9 lbs Disposable Canister
NV12-030C(R)
30 lbs Disposable Canister
NV12-140C(R)
140 lbs Returnable Canister
NV12-300C(R)
300 lbs Returnable Canister

All available in Clear (C) or Red (R)

#### KEY FEATURES

- · Specifically designed for Air Assist Spray
- No ODS (Ozone depleting substances)
- Non-Chlorinated Solvent
- Nevamar Bond Performance
- · High Temperature Resistance
- Fast Tack
- · Water Resistan

**Disclaimer of Warranty:** Nevamar expressly disclaims all warranties either expressed or implied, including but not limited to merchantability and fitness for particular purpose. User is responsible for determining this product is fit for specific purpose and application method and assumes all risk and liability herewith. Manufacturer liability is limited to replacement of product or reimbursement of purchase cost, at our discretion. This provision relates to all sales and cannot be modified.

Mfd. for: Nevamar (855) 497-0700

See MSDS Data Sheet for Proper Handling and Safety Information